



N32POE

32 channel NVR 16 POE



Key Features

- Up to 32-ch IP cameras access
- Up to 1-ch@12MP/32-ch@D1 decoding capacity
- Support face recognition and multi-objective recognition
- Support 2 HDMI and 1 VGA interface
- 4 SATA hard disk each up to 16TB
- 2 RJ45 10M/100M/1000M network interface
- Plug & Play with 16 PoE interface
- Support RAID /5/6/10; Smart search & playback

Specifications

Video Input	
IP Camera Input	32 Channel
Incoming Bandwidth	320Mbps
Outgoing Bandwidth	320Mbps
Video Output	
HDMI 1 Output	3840 × 2160, 1920 × 1080, 1280 × 1024, 1024 × 768
HDMI 2 Output	1920 × 1080, 1280 × 1024, 1024 × 768
VGA Output	1920 × 1080, 1280 × 1024, 1024 × 768
Different Source Output	Support
Decoding Capacity	1ch 12MP, 4ch 4MP, 9ch 1080P, 16ch D1, 32ch D1
Dual Stream	Support
Multi-screen Display	1st Screen: 1/4/8/9/16/32/36 2nd Screen: 1/4/8/9/16
AI Recognition	
Face Comparison	Real-time captured and display faces comparison results (registrant (name and ID), stranger, channel, similarity)
Multi-objective	Real-time captured and display vehicle, human body, non-motor vehicle, license plates image, and faces comparison results (registrant, stranger, channel, similarity)
Smart Search	Time, Properties, Pictures, License plate
Trigger Events	Buzzer, Alarm push, Alarm prompt, Email, Alarm Out, Compare the result simultaneously, etc.
Perimeter Protection	Support
Intrusion	Support alarm triggering by specified target types (human and vehicle)

N32POE

32 channel NVR 16 POE

Recording	
Resolution	8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.
Recording Mode	Manual, Schedule (Regular, Continuous), Event
Trigger Events	Motion Detection, Video Loss, Alarm in, IVS
Playback and Backup	
Sync Playback	16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Backup Mode	USB Device, Network, eSATA
Network	
Network Protocol	HTTP, HTTPS, TCP/IP, IPv4, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE
Remote Users	8 users
Smart Phone	iPhone, iPad, Android
Interoperability	ONVIF, SDK, CGI
Storage	
Disk Array	Array Type
RAID	RAID 5, RAID 6, RAID 10
Interface	
HDD Interface	4 SATA interfaces, up to 16TB capacity for each disk
Network Interface	2 × RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
PoE Interface	16x RJ-45 10/100Mbps, 802.3af/at, max 140W
eSATA	1 eSATA Interface
Audio In/Out	1/1
Alarm In/Out	6/2
USB Interface	Front panel: 2 × USB 2.0, Rear panel: 1 × USB 3.0
RS-485/ RS-232 Interface	Support/ Support
General	
Power Supply	100 to 240VAC
Power Consumption	< 15 W (without HDD)
Operating Conditions	-10°C to 50°C (14°F to 122°F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	40 × 368.3 × 70 mm (17.32 × 14.5 × 2.76 inch)
Net Weight	4.65 kg (10.25 lb) without HDD