

BCS-L-DIP45VSR4-Ai1(2)

Index: **11887** GTIN13/EAN13: 5904890711396

URL: <https://bcs.pl/gb/5mpx/3769-bcs-l-dip45vsr4-ai12-5904890711396.html>



- 5Mpx dome IP camera
- 1/2.7" PS CMOS sensor
- SkyLight technology
- 2.7-13.5 mm motorised zoom lens
- WDR 120dB
- IR 40m
- Alarm 1/1, audio 1/1, microphone
- IP67, IK10 housing
- Built-in smart features



BCS-L-DIP45VSR4-Ai1(2)

Product Details

Product	BCS-L-DIP45VSR4-Ai1(2)
Product line	BCS LINE
Camera type	Dome
Resolution	5 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	2960(H)×1688(V)
RAM	256MB
ROM	128MB
Lens	motozoom
Focal length	2.7~13.5 mm
Aperture	F1.5
Focus	Auto / manual
Iris	Auto
Optical zoom	5×
Digital zoom	16×
Angle of view	H: 113°~31° V: 58°~18° D: 138°~36°
DORI	Detect 64~210m / Observe 26~84m / Recognize 13~42m / Identify 6~21m
Min illumination	0.007Lux(Color,F1.5,30IRE) 0.0007Lux(F1.5,B/W,30IRE) 0Lux(IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	2
Resolutions	5M(2960×1668) /4M(2880×1620)(2688×1520)(2560×1440) /3M(2304×1296)(2048×1536) /2M(1920×1080) /720P(1280×720) /D1(704×576/704×480) /VGA(640×480) /CIF(352×288/352×240)
Main stream	2960×1668(1~20fps) 2688×1520(1~25fps)
Second stream	704×576(1~25fps) 704×480(1~30fps)
Bitrate	H.264: 32 Kbps~8192 Kbps H.265: 12 Kbps~8192 Kbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED
IR range	40m
Microphone	Yes
Audio in	1
Audio out	1
Audio compression	G.711A / G.711Mu / G.726 / PCM
Alarm in	1

Alarm out	1
Storage	FTP, SFTP, NAS
Memory card slot	microSD 256GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 7.4W
Housing color	White
IP class	IP67
IK10	Yes
Working environment	-30°C~+60°C max 95% RH
Dimensions	Ø122×93.4mm
Weight	0.5 kg
Box dimensions in mm (W×D×H)	156×156×137
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD Plus

BCS-L-DIP45VSR4-Ai1(2)

Accessories

BCS-AD2M3V



BCS-L-UD1



BCS-L-AD2M3V



BCS-L-UWS3

