

BCS-L-NVR3208R-A-8K-Ai2

Index: **13027** GTIN13/EAN13: 5904890716674

URL: <https://bcs.pl/gb/32-channel/4628-bcs-l-nvr3208-a-8k-ai2-5904890716674.html>



- 32-channel IP recorder
- AcuPick technology
- Supports 8 hard drives
- RAID
- Support for 32Mpx IP cameras
- 16/8 alarm channels, 1/2 audio channels
- 2xHDMI 8K / 2xVGA outputs
- Built-in smart features



BCS-L-NVR3208R-A-8K-Ai2

Product Details

Product	BCS-L-NVR3208R-A-8K-Ai2
Product line	BCS LINE
System	IP
Pentaplex function	Live view / recording / playback / archiving / remote access
Channels	32
HDD support	8
HDD capacity	20 TB
RAID type	0/1/5/6/10
Record mode	Continuous, manual, alarm, motion detection, schedule, Ai
Max recording resolution	32 Mpx
Incoming bandwidth	448Mbps(200Mbps Ai)
Outgoing bandwidth	448Mbps(200Mbps Ai)
Recording bandwidth	448Mbps(200Mbps Ai)
Display efficiency	2×32M@25fps / 2×24M@25fps / 5×16M@30fps / 6×12M@30fps / 10×8M@30fps / 13×6M@30fps / 16×5M@30fps / 20×4M@30fps / 32×2M@30fps Ai: 1×32M@25fps / 2×24M@25fps / 4×16M@30fps / 5×12M@30fps / 8×8M@30fps / 10×6M@30fps / 12×5M@30fps / 16×4M@30fps / 32×2M@30fps
Recording resolutions	32M / 24M / 16M / 12M / 8M / 6M / 5M / 4M / 3M / 2M / 1.3M / 720P / D1 / CIF / QCIF
Video compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG
HDMI out	2×HDMI8K
VGA out	2×VGA
HDMI display resolutions	7680×4320 / 3840×2160 / 1920×1080 / 1280×1024 / 1280×720
VGA display resolutions	1920×1080 / 1280×1024 / 1280×720
Display split	Main screen: 1/4/8/9/16/25/36 Secondary screen: 1/4/8/9/16
Recording	continuous recording, with motion detection (with recording before and after detection), alarm (with pre- and post-alarm recording), cyclic (overwriting), Ai
Synchronous playback	1/4/9/16
Archiving	Possibility to download material to external media such as USB FLASH, USB HDD
User connections	128
Interfaces	2×USB2.0, 2×USB3.0, eSATA
Serial port	RS232, RS485, RS422
Audio in	1
Audio out	2
Audio compression	G.711A / G.711U / G.726 / PCM
Alarm in	16
Alarm out	8
Alarm	Motion detection, signal lost,, sabotage, scene change, PIR, IPC, Ai functions, offline, HDD, IP, MAC, login
Support	Local, Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Network	2×RJ-45 10/100/1000Mbps
Compatibility	ONVIF(S/G/T/M), support for cameras from other manufacturers
PTZ control	Intelligent 3D positioning with PTZ cameras BCS LINE series.
Protocols	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UDP, NTP, FTP, SFTP, DHCP, DNS, SMTP, UPnP, DDNS, SNMP, Alarm Server, IP Search, Multicast, P2P, Auto Registration, iSCSI
Power supply	100~240V AC
Power consumption (without HDD)	max 13W

Working environment	-10°C~+55°C max 93% RH
Casing	2U
Dimensions mm (W×D×H)	440×458×95
Box dimensions in mm (W×D×H)	570×570×226
Weight (without HDD)	6.27 kg
POS	Posnet
Ai - Intelligent functions from recorder	Face detection, face identification, perimeter protection (person/vehicle recognition), metadata, SMD Plus
Ai - Intelligent functions from camera	Face detection, face recognition, metadata (human/vehicle classification), SMD Plus, people gathering, people counting, ARTR, vehicle density, object monitoring, heat map
Ai - Perimeter protection	8 channels from the recorder, 10 rules per channel / 32 channels from cameras
Ai - Face detection	4 channels from nvr (12 images/s) / 32 channels from camera / face attributes (gender, age, glasses, expression, mask, beard)
Ai - Face recognition	24 detection channels from IPC + identification from NVR (24 images/s) / 4 detection channels from NVR + identification from NVR (24 images/s) / 32 channels of identification from IPC / up to 20 face databases, 30 thousand images, up to 3.75GB
Ai - Metadata	4 ch from NVR / 32 ch from IPC / Person attributes (clothes color, type of clothes, headgear, bag, age, gender, umbrella) / motor vehicle attributes (license plate, plate color, vehicle type, logo, telephone, number of people, seat belts)
Ai - ARTR	32 channels from nvr / black and white list 20k records
Ai - SMD - Smart Motion Detection	16 channels from the recorder / 32 channels from cameras
Ai - Smart search	AcuPick technology - intelligent search for human/vehicle objects in the recording history with camera with the AcuPick function
Accessories included	Rack mounts, mouse, IEC C13 power cable, RJ45 cable, hard drive power cable, SATA hard drive cable