

## BCS-B-SP0402

Index: **8607** GTIN13/EAN13: 5904890705777

URL: <https://bcs.pl/gb/poe-switches-/1248-bcs-b-sp0402-5904890705777.html>



### 4-port PoE switch

- exPoE technology
- 4xPoE 100Mbps af/at
- 2xRJ45 uplink 100Mbps
- Total power: 60W
- modes: standard/VLAN/extend/QoS/PoE



### Description

6-port switch (4 × PoE) 100Mbps with 4 operating modes

BCS-B-SP0402

Product Details

|                        |                                                                                                       |
|------------------------|-------------------------------------------------------------------------------------------------------|
| Product                | BCS-B-SP0402                                                                                          |
| Product line           | BCS BASIC                                                                                             |
| PoE ports              | 4×RJ45 100Mbps                                                                                        |
| Uplink ports           | 2×RJ45 100Mbps                                                                                        |
| Standard IEEE          | 802.3af / 802.3at                                                                                     |
| Transfer               | 10/100Mbps half-duplex, full-duplex, auto-negotiation, auto MDI/MDIX                                  |
| Packet forwarding rate | 1.48Mpps                                                                                              |
| Capacity               | 1.2Gbps                                                                                               |
| STANDARD mode          | 100m                                                                                                  |
| VLAN mode              | VLAN mode ports 1-4 isolated                                                                          |
| EXTEND mode            | EXTEND mode ports 1-4 support transmission 250m 10Mbps (cat5e, cat6)                                  |
| QoS mode               | QOS Quality Of Service - priority video pockets                                                       |
| PoE mode               | Monitoring ports supply PoE devices and automatic restart with power supply cut when not responding   |
| PoE pin                | 1,2(+), 3,6(-)                                                                                        |
| LED status             | PWR(yellow): power supply connected, LINK/ACT(green): device connected, PoE(yellow): power supply PoE |
| PoE switch power       | 60W max 36W/port                                                                                      |
| Power supply           | 52V DC 1.15A                                                                                          |
| Working environment    | 0°C~+40°C max 90% RH                                                                                  |
| Weight                 | 0.5 kg                                                                                                |
| Casing                 | Desktop                                                                                               |
| Dimensions mm (W×D×H)  | 125×75×27mm                                                                                           |