

BCS-B-SP04G02G

Index: **8609** GTIN13/EAN13: 5904890705791

URL: <https://bcs.pl/gb/poe-switches-/1249-bcs-b-sp04g02g-5904890705791.html>



4-port PoE switch

- exPoE technology
- 4xPoE 1Gbps af/at
- 2xRJ45 1Gbps uplink
- Total power 60W
- modes: standard/VLAN/extend/QoS/PoE



Description

6-port Gigabit switch (4 × PoE) with 4 operating modes

BCS-B-SP04G02G

Product Details

Product	BCS-B-SP04G02G
Product line	BCS BASIC
PoE ports	4×RJ45 1Gbps
Uplink ports	2×RJ45 1Gbps
Standard IEEE	802.3af / 802.3at
Transfer	10/100/1000Mbps half-duplex, full-duplex, auto-negotiation, auto MDI/MDIX
Packet forwarding rate	1.48Mpps
Capacity	12Gbps
STANDARD mode	100m
VLAN mode	VLAN mode ports 1-4 isolated
EXTEND mode	EXTEND mode ports 1-4 support transmission 250m 10Mbps (cat5e, cat6)
QoS mode	QOS Quality Of Service - priority video pockets
PoE mode	Monitoring ports supply PoE devices and automatic restart with power supply cut when not responding
PoE pin	1,2(+), 3,6(-)
LED status	PWR(yellow): power supply connected, LINK/ACT(green): device connected, PoE(yellow): power supply PoE
PoE switch power	60W max 36W/port
Power supply	52V DC 1.15A
Working environment	0°C~+40°C max 90% RH
Weight	0.5 kg
Casing	Desktop
Dimensions mm (W×D×H)	125×75×27mm