

BCS-B-SP0802G

Index: **12410** GTIN13/EAN13: 5904890713550

URL: <https://bcs.pl/gb/poe-switches-/4195-bcs-b-sp0802g-5904890713550.html>



8-port PoE switch

- exPoE technology
- 8xPoE 100Mbps af/at
- 2xRJ45 1Gbps uplink
- Total power: 96W
- modes: standard/VLAN/extend/QoS/PoE



BCS-B-SP0802G

Product Details

Product	BCS-B-SP0802G
Product line	BCS BASIC
PoE ports	8×RJ45 100Mbps
Uplink ports	2×RJ45 1Gbps
Standard IEEE	802.3af / 802.3at
Transfer	10/100/1000Mbps half-duplex, full-duplex, auto-negotiation, auto MDI/MDIX
Packet forwarding rate	4.17Mpps
Capacity	5.6Gbps
MAC table	2K
STANDARD mode	100m
VLAN mode	VLAN mode ports 1-8 isolated
EXTEND mode	EXTEND mode ports 1-8 support transmission 250m 10Mbps (cat5e, cat6)
QoS mode	QOS Quality Of Service - priority video pockets
PoE mode	Monitoring ports supply PoE devices and automatic restart with power supply cut when not responding
PoE pin	1,2(+), 3,6(-)
LED status	PWR(yellow): power supply connected, LINK/ACT(green): device connected, PoE(yellow): power supply PoE
PoE switch power	96W max 30W/port
Protection	6kV surge protection
Power supply	52V DC 1.85A
Working environment	0°C~+40°C max 90% RH
Weight	0.8 kg
Casing	Desktop
Dimensions mm (W×D×H)	184×94×27mm