

BCS-B-ISP08G-2SFP

Index: **11666** GTIN13/EAN13: 5904890709942

URL: <https://bcs.pl/gb/poe-switches-/3597-bcs-b-isp08g-2sfp-5904890709942.html>



8-port industrial PoE switch for DIN rail mounting

- 8xPoE 1Gbps af/at
- exPoE technology
- 2x 1Gbps SFP uplinks
- Total power 250W (31.25W per port)
- Modes: standard/VLAN/extend/QoS/PoE
- The kit does not include a power supply



BCS-B-ISP08G-2SFP

Product Details

Product	BCS-B-ISP08G-2SFP
Product line	BCS BASIC
PoE ports	8×RJ45 1Gbps
Uplink ports	2×SFP 1Gbps
Standard IEEE	802.3 / 802.3u / 802.3ab / 802.3z / 802.3af / 802.3at
Transfer	10/100/1000Mbps half-duplex, full-duplex, auto-negotiation, auto MDI/MDIX
Packet forwarding rate	14.8Mpps
Capacity	20Gbps
MAC table	4K
Packet buffer memory	2Mbit
STANDARD mode	100m
VLAN mode	VLAN mode ports 1-8 isolated
EXTEND mode	EXTEND mode ports 1-8 support transmission 250m 10Mbps (cat5e, cat6)
QoS mode	QOS Quality Of Service - priority video pockets
PoE mode	Monitoring ports supply PoE devices and automatic restart with power supply cut when not responding
PoE pin	1,2(+), 3,6(-)
LED status	LINK/ACT(green): connected device, PoE(yellow): device powered by PoE
PoE switch power	250W
Protection	(ESD): ±8kV (contact), ±15kV (air), (EFT): Power Port: ±4kV; Data Port: ±2kV, (Surge): Power Port: ±2kV/DM, ±4kV/CM; Data Port: ±6kV
Power supply	48~56V DC
Working environment	-40°C~+70°C max 90% RH
Weight	1 kg
Casing	DIN rail
Dimensions mm (W×D×H)	150×127×40mm

BCS-B-ISP08G-2SFP

Accessories

BCS-ZA4820

