

BCS-B-SP08G-2SFP-M

Index: **8991** GTIN13/EAN13: 5904890705845

URL: <https://bcs.pl/gb/poe-switches-/1252-bcs-b-sp08g-2fsp-m-5904890705845.html>



8-port managed PoE switch

- exPoE technology
- 8xPoE 1Gbps af/at
- 2x 1Gbps SFP uplinks
- Total power 150W
- Modes: standard/VLAN/extend/QoS/PoE



Description

8-port managed switch (8 × PoE) 1000Mbps + 2 × Gigabit SFP with 4 operating modes

BCS-B-SP08G-2SFP-M

Product Details

Product	BCS-B-SP08G-2SFP-M
Product line	BCS BASIC
PoE ports	8×RJ45 1Gbps
Uplink ports	2×SFP 1Gbps
Managed	Yes
Management port	1×RJ45
Management functions	port conf, storm control, energy, poe, power, timing, poe ai, layer2, mac, vlan, link aggr, mstp, loop protection, dhcp snoop, igmp snoop, 802.1x, qos, acl, snmp, rmon, lldp, ntp set, anti attack, sys manage, user, service, conf man, firm upgr, diag
Standard IEEE	802.3af / 802.3at
Transfer	10/100/1000Mbps half-duplex, full-duplex, auto-negotiation, auto MDI/MDIX
Packet forwarding rate	14.8Mpps
Capacity	20Gbps
STANDARD mode	100m
VLAN mode	VLAN mode ports 1-8 isolated
EXTEND mode	EXTEND mode ports 1-8 support transmission 250m 10Mbps (cat5e, cat6)
QoS mode	QOS Quality Of Service - priority video pockets
PoE mode	Monitoring ports supply PoE devices and automatic restart with power supply cut when not responding
PoE pin	1,2(+), 3,6(-)
LED status	PWR(red): power supply connected, LINK/ACT(green): device connected, PoE(yellow): device powered from PoE, SYS(green blink): System status
PoE switch power	150W max 46W/port
Power supply	100~240V AC
Working environment	0°C~+40°C max 90% RH
Weight	1.3 kg
Casing	1U
Dimensions mm (W×D×H)	285×180×44mm