

BCS-B-SP2402G-1SFP

Index: **11287** GTIN13/EAN13: 5904890708464

URL: <https://bcs.pl/gb/poe-switches-/3403-bcs-b-sp2402g-1sfp-5904890708464.html>



24-port PoE switch

- exPoE technology
- 24xPoE 100Mbps af/at (Base-TX)
- 2xRJ45 1Gbps uplink
- 1x SFP uplink 1 Gbps
- Total power 250W, PoE budget for 24 cameras
- Modes: standard/VLAN/extend/QoS/PoE
- Store-and-Forward transmission



BCS-B-SP2402G-1SFP

Product Details

Product	BCS-B-SP2402G-1SFP
Product line	BCS BASIC
PoE ports	24×RJ45 100Mbps
Uplink ports	2×RJ45 1Gbps / 1×SFP 1Gbps
Standard IEEE	802.3af / 802.3at
Transfer	10/100/1000Mbps half-duplex, full-duplex, auto-negotiation, auto MDI/MDIX
Packet forwarding rate	6.55Mpps
Capacity	8.8Gbps
STANDARD mode	100m
VLAN mode	VLAN mode ports 1-24 isolated
EXTEND mode	EXTEND mode ports 1-8 support transmission 250m 10Mbps (cat5e, cat6)
QoS mode	QOS Quality Of Service - priority video pockets
PoE mode	Monitoring ports supply PoE devices and automatic restart with power supply cut when not responding
PoE pin	1,2(+), 3,6(-)
LED status	PWR(red): power supply connected, LINK/ACT(green): device connected, PoE(yellow): device powered from PoE
PoE switch power	250W max 30W/port
Power supply	100~240V AC
Working environment	0°C~+40°C max 90% RH
Installation	Possibility of mounting in a 19" rack cabinet (handles included)
Weight	2.4 kg
Casing	1U
Dimensions mm (W×D×H)	440×180×44mm