

BCS-L-TIP15FSR3L3-W-Ai

Index: **13085** GTIN13/EAN13: 5904890717060

URL: <https://bcs.pl/gb/5mpx/4758-bcs-l-tip15fsr3l3-w-ai-5904890717060.html>



- 5Mpx IP bullet camera
- 1/2.7" PS CMOS sensor
- 802.11ax Wi-Fi technology
- Nightcolour technology
- 2.8 mm fixed lens
- Microphone
- IR 30m, WhiteLight 30m
- IP67-rated housing
- Intelligent motion detection with human/vehicle recognition
- Wi-Fi connection and network configuration: automatically with the recorder in AP mode, or manually via the WebService using a web browser
- Compatibility

[-BCS-L-NVR0401-4KE-W\(2L\)](#)

[-BCS-L-NVR0801-4KE-W\(2L\)](#)



BCS LINE

BCS-L-TIP15FSR3L3-W-Ai

Product Details

Product	BCS-L-TIP15FSR3L3-W-Ai
Product line	BCS LINE
Camera type	Wi-Fi
Resolution	5 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	2880(H)×1620(V)
Lens	fixed
Focal length	2.8 mm
Aperture	F1.6
Focus	fixed
Iris	fixed
Angle of view	H: 104° V: 56° D: 124°
Min illumination	0.007Lux(Color,F1.6,30IRE) 0.0007Lux(F1.6,B/W,30IRE) 0Lux(IR)
White balance	(AWB) Auto / manual
WDR	DWDR
Backlight compensation	DWDR
Shutter	Auto
Gain control	Auto
Image rotate	Flip 0°/180°
Stream support	2
Main stream	2880×1620(1~25/30fps)
Second stream	640×360(1~25/30fps)
Bitrate	H.264: 32 kbps~6144kbps H.265: 12 kbps~6144kbps
Video compression	H.265 / H.264 / H.264H / H.264B / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
NightColor	Yes
Microphone	Yes
Audio compression	G.711a / G.711mu / PCM
Memory card slot	microSD 256GB
Network	RJ-45 10/100 Mbps
Wi-Fi	802.11b/g/n/ax 2.4GHz
Compatibility	ONVIF(S/G/T)
Power supply type	12V DC
Power consumption	max 4.3W
Housing color	White
IP class	IP67
Working environment	-40°C~+60°C max 95% RH
Dimensions	172.4×83.3×75mm

Weight	0.3 kg
Casing	Metal + Plastik
Box dimensions in mm (W×D×H)	231×122×102
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - SMD - Smart Motion Detection	Intelligent Ultra Motion Detection with human/vehicle recognition
Accessories included	power supply 12V DC

BCS-L-TIP15FSR3L3-W-Ai**Accessories**

BCS-ADU100



BCS-ADU125



BCS-L-AT356



BCS-L-AT3



BCS-L-AT135(2)

