

BCS-L-EIP14FSR3L3-AI

Index: **13352** GTIN13/EAN13: 5904890718333

URL: <https://bcs.pl/gb/4mpx/4747-bcs-l-eip14fsr3l3-ai-5904890718333.html>



- 4Mpx dome IP camera
- 1/2.9" PS CMOS sensor
- SkyLight technology
- WDR 120dB
- 2.8mm fixed lens
- IR 30m, WhiteLight 30m
- Microphone
- IP67-rated housing
- Intelligent motion detection with human recognition



BCS-L-EIP14FSR3L3-AI

Product Details

Product	BCS-L-EIP14FSR3L3-AI
Product line	BCS LINE
Camera type	Dome
Resolution	4 Mpx
Sensor	1/2.9" CMOS
Scanning system	Progressive Scan
Pixels	2560(H)×1440(V)
RAM	128MB
ROM	128MB
Lens	fixed
Focal length	2.8 mm
Aperture	F1.6
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H :94° V: 52° D: 111°
DORI	Detect 64m/ Observe 25m/ Recognize 13m/ Identify 6m
Min illumination	0.006Lux(Color,F1.6,30IRE) 0.0006Lux(F1.6,B/W,30IRE) 0Lux(IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
RoI	Region of Interest
Image rotate	Mirror, Flip 0°/180°
Stream support	2
Resolutions	4M(2560×1440) /3M(2304×1296) /2M(1920×1080) /1.3M(1280×960) /720P(1280×720) /D1(704×576/704×480) /VGA(640×480) /CIF(352×288/352×240)
Main stream	2560×1440(1~25/30fps)
Second stream	704×576(1~25fps) 704×480(1~30fps)
Bitrate	H.264: 32 kbps~4096 kbps H.265: 12 kbps~4096 kbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
Microphone	Yes
Audio compression	G.711A / G.711Mu / G.726 / PCM
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4

Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 5.7W
Housing color	White
IP class	IP67
Working environment	-40°C~+60°C max 95% RH
Dimensions	Ø106×94mm
Weight	0.33 kg
Box dimensions in mm (W×D×H)	122×119×111
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - SMD - Smart Motion Detection	Intelligent motion detection with human recognition

BCS-L-EIP14FSR3L3-AI

Accessories

BCS-UD3



BCS-L-ADMM



BCS-L-UD2



BCS-L-AT48



BCS-L-AT135(2)

