BCS-L-EIP28FCL3P-Ai1

Index: **13344** GTIN13/EAN13: 5904890718371
URL: https://bcs.pl/gb/8mpx/4746-bcs-l-eip28fcl3p-ai1-5904890718371.html





- 8Mpx dome IP camera
- 1/1.8" PS CMOS sensor
- NightColor 2.0 technology
- 2.8 mm fixed lens
- WDR 120 dB
- Microphone
- Whitelight 30m
- IP67-rated housing
- Built-in smart features

POLSKA MARKA

BCS LINE

BCS-L-EIP28FCL3P-Ai1

Product Details

Product	BCS-L-EIP28FCL3P-Ai1
Product line	BCS LINE
Camera type	Dome
Resolution	8 Mpx
Sensor	1/1.8'' CMOS
Scanning system	Progressive Scan
Pixels	3840(H)×2160(V)
RAM	256MB
ROM	128MB
Lens	fixed
Focal length	2.8 mm
Aperture	F1.0
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H: 110° V: 59° D: 131°
DORI	Detect 84m/ Observe 33.6m/ Recognize 16.8m/ Identify 8.4m
Min illumination	0.0004Lux@F1.0
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
LDC	Lens Distortion Correction
RoI	Region of Interest
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	2
Resolutions	8M(3840×2160) 6M(3072×2048) 5M(3072×1728) 4M(2880×1620/2688×1520) 3M(2048×1536/2304×1296) 1080p(1920×1080) 1.3M(1280×960) 720p(1280×720) D1(704×576/704×480) VGA(640×480) CIF(352×288/352×240)
Main stream	3840×2160(1~20fps) 2688×1520(1~25/30fps)
Second stream	704×576(1~25fps) 704×480(1~30fps)
Bitrate	H.264: 32 kbps~8192kbps H.265: 12 kbps~8192kbps
Video compression	H.265+ / H.265 / H.264+ / H.264 / H.264H / H.264B / MJPEG
Illuminator type	WhiteLight
WhiteLight range	30m
NightColor	NightColor 2.0
Microphone	Yes
Audio compression	G.711A / G.711Mu / G.726 / PCM
Storage	FTP, SFTP, NAS
Memory card slot	microSD 256GB

Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, P2P, Bonjour, Auto Registration
Network security	Digest, WSSE, Account lockout, Security logs, IP/MAC filtering, Generation and importing of X.509 certification, Syslog, HTTPS, 802.1x, Trusted boot, Trusted execution, Trusted upgrade, Session security, Security warning
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 6.4W
Housing color	White
IP class	IP67
Working environment	-40°C~+60°C max 95% RH
Box dimensions in mm (W×D×H)	156×156×137
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analisis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD Plus
Ai - Smart search	Work together with Smart NVR to perform refine intelligent search, event extraction and merging to event videos

BCS-L-EIP28FCL3P-Ai1

Accessories

BCS-ATU-B



BCS-ADU-B




BCS-UD3



BCS-ADU125



BCS-ADU170



BCS-L-ADMM



BCS-L-UD2



BCS-L-AT48



BCS-L-AT135(2)

