

BCS-L-TIP46VCR6L6-Ai1-G

Index: **12715** GTIN13/EAN13: 5904890714847

URL: <https://bcs.pl/gb/6mpx/4285-bcs-l-tip46vcr6l6-ai1-g-5904890714847.html>



- 6Mpx IP bullet camera
- 1/2.7" PS CMOS sensor
- NightColor technology
- 2.7-13.5 mm motorised zoom lens
- WDR 120dB
- Alarm 1/1 Audio 1/1
- Microphone
- IR illuminator 60m
- White light 60m
- IP67 housing
- Built-in smart features



BCS-L-TIP46VCR6L6-Ai1-G

Product Details

Product	BCS-L-TIP46VCR6L6-Ai1-G
Product line	BCS LINE
Camera type	Bullet
Resolution	6 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	3288(H)×1850(V)
RAM	256MB
ROM	128MB
Lens	motozoom
Focal length	2.7~13.5 mm
Aperture	F1.5
Focus	Auto / manual
Iris	Auto
Optical zoom	5×
Digital zoom	16×
Angle of view	H: 114°~32° V: 58°~17° D: 138°~36°
DORI	Detect 64~210m / Observe 26~84m / Recognize 13~42m / Identify 6~21m
Min illumination	0.007Lux(Color,F1.5,30IRE) 0.0007Lux(B/W,F1.5,30IRE) 0Lux(IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
RoI	Region of Interest
Image rotate	Mirror, Flip 0°/90°/180°/270°
Stream support	2
Resolutions	6M(3288×1850/3200×1800) 5M(2880×1620) 4M(2688×1520) 3M(2304×1296) 1080p(1920×1080) 720p(1280×720) D1(704×576/704×480) VGA(640×480) CIF(352×288/352×240)
Main stream	3288×1850@(1~20fps) 2688×1520@(1~25/30fps)
Second stream	704×576(1~25fps) 704×480(1~30fps)
Bitrate	H.264: 32 Kbps~8192 Kbps H.265: 12 Kbps~8192 Kbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
IR range	60m
WhiteLight range	60m
NightColor	Yes
Microphone	Yes
Audio in	1

Audio out	1
Audio compression	G.711A / G.711Mu / G.726 / PCM
Alarm in	1
Alarm out	1
Storage	FTP, SFTP
Memory card slot	microSD 256GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour, P2P
Network security	Video / Firmware / Configuration encryption, Digest, WSSE, Account lockout, Security logs, IP/MAC filtering, Generation and importing of X.509 certification, syslog, HTTPS, 802.1x, Trusted boot / execution / upgrade, Session security, Security warning
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 12.7W
Housing color	White
IP class	IP67
Working environment	-30°C~+60°C max 95% RH
Dimensions	238.5mm × 90.7mm × 90.7mm
Weight	0.76 kg
Casing	Metal
Box dimensions in mm (W×D×H)	285×120×123
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD Plus

BCS-L-TIP46VCR6L6-Ai1-G

Accessories

BCS-ATU-G



BCS-ADU-G



BCS-ADU100



BCS-ADU125



BCS-L-AT356



BCS-L-AT5V



BCS-L-AT135-G(2)

