

BCS-L-NVR0802-A-4KE(2)

Index: 11489

GTIN13/EAN13: 5904890709102

URL: <https://bcs.pl/gb/8-channel/3522-bcs-l-nvr0802-a-4ke2-5904890709102.html>

Product Details

Product	BCS-L-NVR0802-A-4KE(2)
Brand	BCS LINE
System	IP
Pentaplex function	Live view / recording / playback / archiving / remote access
Channels	8
HDD support	2
HDD capacity	16 TB
Max recording resolution	16 Mpx
Incoming bandwidth	256Mbps(180Mbps Ai)
Outgoing bandwidth	256Mbps(180Mbps Ai)
Display efficiency	2×16M(30fps) / 2×12M(30fps) / 4×8M(30fps) / 6×5M(30fps) / 8×4M(30fps) / 1×16M Ai(30fps) / 2×12M Ai(30fps) / 3×8M Ai(30fps) / 4×5M Ai(30fps) / 6×4M Ai(30fps) / 8×2M Ai(30fps)
Recording resolutions	16M / 12M / 8M / 6M / 5M / 4M / 3M / 2M / 1.3M / 720P / D1 / CIF
Video compression	H.265+ / H265 / H.264+ / H.264 / MJPEG
Video output	HDMI4K/VGA
HDMI display resolutions	3840×2160 / 1920×1080 / 1280×1024 / 1280×720 / 1024×768
VGA display resolutions	1920×1080 / 1280×1024 / 1280×720 / 1024×768
Display split	1/4/8/9
Synchronous playback	1/4/8
Archiving	Possibility to download material to external media such as USB FLASH, USB HDD
Interfaces	1×USB2.0, 1×USB3.0
Audio in	1

Audio out	1
Audio compression	G.711A / G.711U / G.726 / PCM
Alarm in	4
Alarm out	2
Support	Local, Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Network	RJ-45 10/100/1000Mbps
Compatibility	ONVIF(S/G/T), support third party cameras
Protocols	HTTP, HTTPS, TCP/IP, IPv4/IPv6, UPnP, SNMP, UDP, SMTP, NTP, DHCP, DNS, IP Filter, PPPoE, DDNS, FTP, Alarm Server, IP Search, P2P, auto register
Power supply	12V DC
Power consumption (without HDD)	max 10W
Working environment	-10°C~+55°C max 93% RH
Casing	1U
Dimensions (W×D×H)	375×282×53mm
Weight (without HDD)	1.5 kg
Ai - Intelligent functions from recorder	Face detection, face recognition, perimeter protection (human/vehicle classification), SMD Plus
Ai - Intelligent functions from camera	Face detection, face identification, perimeter protection (human/vehicle classification), SMD Plus, people counting, ARTR, heat map
Ai - Perimeter protection	2 channels from nvr, 10 rules for channel / 8 channels from camera
Ai - Face detection	1 channel from nvr (12 images/s) / 8 channels from camera / face attributes (gender, age, glasses, expression, mask, beard)
Ai - Face recognition	8 kanałów detekcji z kamery + identyfikacja z rejestratora (12 obrazów/s) / 1 kanał detekcji z rejestratora + identyfikacja z rejestratora (12 obrazów/s) / 8 kanałów identyfikacji z kamer / do 10 baz danych twarzy, 20 tys obrazów, do 2.5GB
Ai - SMD	4 channels from nvr / 8 channels from camera