



BASE-NVR-N16H2


16CH 2HDD 4K NVR




KEY FEATURE

- Up to 16-ch IP cameras access
- Up to 160 Mbps incoming/outgoing bandwidth
- Up to 1-ch @ 12MP/4-ch @ 4MP/8-ch @ 1080P/16-ch D1 decoding capacity
- Support mask detection, face recognition and multi-objective recognition
- Support VCA alarm linkage
- Up to 4-ch perimeter protection
- Support 1 HDMI and 1 VGA interface
- Support ANR

DIMENSIONS (MM)



CYBERSECURITY



REAR PANEL



PLUG AND PLAY



FREE STANDARD EMBEDDED ANALYTIC



SMART MOTION DETECTION





SPECIFICATION	
VIDEO INPUT	
IP Camera Input	16 Channel
Incoming Bandwidth	160 Mbps (112Mbps with AI enabled)
Outgoing Bandwidth	160 Mbps (112Mbps with AI enabled)
VIDEO OUTPUT	
HDMI Output	3840×2160, 1920 1080, 1280×1024, 1024×768
VGA Output	1920×1080, 1280×1024, 1024×768
Different Source Output	Support
Decoding Capacity	1ch 12MP, 4ch 4MP, 8ch 1080P, 16ch D1 Enable Local Intelligence: 1ch 8MP, 4ch 1080P, 8ch D1, 16ch D1
Dual Stream	Support
Multi-screen Display	1/4/9/16
AI RECOGNITION	
Face Comparison	Real-time captured and display faces comparison results (registrant (name and ID), stranger, channel, similarity)
Multi-objective	Real-time captured and display vehicle, human body, non-motor vehicle, license plates image, and faces comparison results (registrant, stranger, channel, similarity)
Smart Search	Time, Properties, Pictures, License plate
Trigger Events	Buzzer, Alarm push, Alarm prompt, Email, Alarm Out, Compare the result simultaneously, etc.
RECORDING	
Resolution	12MP, 8MP, 6MP, 5MP, 4MP, 3MP, 1080P, 720P, D1 etc.
Recording Mode	Manual, Schedule (Regular, Continuous), Event
Trigger Events	Motion Detection, Video Loss, Alarm in, IVS
PLAYBACK AND BACKUP	
Sync Playback	16/9/4/1
Search Mode	Time /Date, Alarm, Picture grid, Event
Backup Mode	USB Device, Network
ALARM	
General Alarm	Motion Detection, Video Loss, Alarm in, Alarm out
Intelligent Analysis (By Camera)	Smoking Detection, Smoke and Fire Detection, Fire Spot Detection, Intrusion, Single/Double Line Crossing, Loitering, Wrong-way, Illegal Parking, People Counting, Smart motion detection, Enter Area, Leave Area, etc.
Abnormal Alarm	Disk Alarm, IP Address Conflict, Network Disconnect
Intelligent Analysis (By NVR)	4-ch intrusion detection, support the accurate detection of human and vehicle
Event Action	Buzzer, Push message to APP, Pop up message to monitor, Full screen, Email, FTP, PTZ, Alarm output, Recording

NETWORK	
Protocols	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UPnP, UDP, RTSP, SMTP, NTP, DNS, DHCP, FTP, P2P, IP Filter, DDNS, 802.1X, SNMP, 3G/4G, PPPoE
Remote Users	8 users
P2P	P2P, Web NAT
Interoperability	ONVIF, SDK, CGI
STORAGE	
ANR	Support
Disk Group	Support
INTERFACE	
HDD Interface	2 SATA, up to 12TB capacity for each disk
Network Interface	2× RJ-45, 10/100/1000 Mbps self-adaptive Ethernet port
HDMI	1
VGA	1
Audio In/Out	1/1
Alarm In/Out	8/1
USB Interface	Front panel: 2× USB 2.0
Reset Button	On-board reset button
GENERAL	
Power Supply	12VDC/3A
Power Consumption	< 15 W (without HDD)
Operating Temperature	-10°C ~ 50°C (14°F ~ 122°F)
Storage Conditions	Less than 90% RH
Certifications	CE/FCC
Dimensions	372×311.2×46.4mm (16.65×12.33×1.83inch)
Net Weight	1.8 kg (3.97 lb) without HDD