

BCS-L-EIP28FCR3L3-AI1-G(2)

Index: **12893** GTIN13/EAN13: 5904890715974

URL: <https://bcs.pl/gb/8mpx/4459-bcs-l-eip28fcr3l3-ai1-g2-5904890715974.html>



- 8Mpx dome IP camera
- 1/2.7" PS CMOS sensor
- NightColor 2.0 technology
- 2.8 mm fixed lens
- WDR 120dB
- Microphone
- IR 30
- Whitelight 30m
- IP67 housing
- Built-in smart features



BCS-L-EIP28FCR3L3-AI1-G(2)

Product Details

Product	BCS-L-EIP28FCR3L3-AI1-G(2)
Product line	BCS LINE
Camera type	Dome
Resolution	8 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	3840(H)×2160(V)
RAM	1GB
ROM	256MB
Lens	fixed
Focal length	2.8 mm
Aperture	F1.4
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H :110° V: 58° D: 132°
DORI	Detect 85m/ Observe 34m/ Recognize 17m/ Identify 9m
Min illumination	0.007Lux(Color,F1.4,30IRE) 0.0007Lux(F1.4,B/W,30IRE) 0Lux(IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB) / SSA
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
LDC	Lens Distortion Correction
RoI	Region of Interest
Defog	Electronic
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	3
Resolutions	8M(3840×2160) 6M(3200×1800) 5M(3072×1728) 4M(2688×1520/2560×1440) 3M(2304×1296) 1080p(1920×1080) 720p(1280×720) D1(704×576/704×480) VGA(640×480) CIF(352×288/352×240)
Main stream	3840×2160(1~25/30fps)
Second stream	1920×1080@(1~25/30 fps)
Third stream	1920×1080@(1~25/30 fps)
Bitrate	H.264: 3 kbps~16384 kbps H.265: 3 kbps~16384 kbps
Video compression	H.265+ / H.265 / H.264+ / H.264 / MJPEG / Ai Coding
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
NightColor	Yes

Microphone	Yes
Audio compression	G.711A / G.711Mu / G.723 / G.726 / PCM
Storage	FTP, SFTP, NAS
Memory card slot	microSD 512GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	8
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, SAMBA, PPPoE, SNMP, P2P
Network security	Video / Firmware / Configuration encryption, Digest, WSSE, Account lockout, Security logs, IP/MAC filtering, Generation and importing of X.509 certification, syslog, HTTPS, 802.1x, Trusted boot / execution / upgrade, Session security, Security warning
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 9.5W
Redundant power	Dual Power Backup
Housing color	Graphite
IP class	IP67
Working environment	-40°C~+60°C max 95% RH
Dimensions	Ø106×93.6mm
Weight	0.5 kg
Box dimensions in mm (W×D×H)	156×156×137
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD 4.0
Ai - Smart search	AcuPick technology - intelligent search for human/vehicle objects in the recording history with a recorder with the AcuPick function
Ai - Large Scale Models	Perimeter protection: increased detection range, reduced false alarms

BCS-L-EIP28FCR3L3-AI1-G(2)

Accessories

BCS-UD2



BCS-UD3




BCS-L-UD2



BCS-L-AT48



BCS-L-AT135-G(2)



BCS-L-ADMM-G

