

BCS-L-DIP14FCR3L3-Ai1

Index: **12550** GTIN13/EAN13: 5904890713963

URL: <https://bcs.pl/gb/4mpx/4169-bcs-l-dip14fcr3l3-ai1-5904890713963.html>



- 4Mpx dome IP camera
- 1/2.9" PS CMOS sensor
- NightColor technology
- 2.8 mm fixed lens
- WDR 120 dB
- Microphone
- IR illuminator 30m
- Whitelight 30m
- IP67 housing
- Built-in smart features



BCS-L-DIP14FCR3L3-Ai1

Product Details

Product	BCS-L-DIP14FCR3L3-Ai1
Product line	BCS LINE
Camera type	Dome
Resolution	4 Mpx
Sensor	1/2.9" CMOS
Scanning system	Progressive Scan
Pixels	2688(H)×1520(V)
RAM	128MB
ROM	128MB
Lens	fixed
Focal length	2.8 mm
Aperture	F1.6
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H: 101° V: 54° D: 120°
DORI	Detect 64m/ Observe 25m/ Recognize 13m/ Identify 6m
Min illumination	0.006Lux(Color,F1.6,30IRE) 0.0006Lux(F1.6,B/W,30IRE) 0Lux(IR)
S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
RoI	Region of Interest
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	2
Resolutions	4M (2688×1520/2560×1440) /3M (2304×1296) /1080p (1920×1080) /1.3M (1280×960) /720p (1280×720) /D1 (704×576/704×480) /VGA (640×480) /CIF (352×288/352×240)
Main stream	2688×1520 @ (1~20 fps)/2560×1440@(1-25/30 fps)
Second stream	704×576@(1~25 fps)/704×480@(1~30 fps)
Bitrate	H.264: 32 Kbps~6144 Kbps H.265: 12 Kbps~6144 Kbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
IR range	30m
WhiteLight range	30m
NightColor	Yes
Microphone	Yes
Audio compression	G.711A / G.711Mu / G.726 / PCM
Storage	FTP, SFTP, NAS

Memory card slot	microSD 256GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP , RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP, P2P
Network security	Video / Firmware / Configuration encryption, Digest, WSSE, Account lockout, Security logs, IP/MAC filtering,Generation and importing of X.509 certification, syslog, HTTPS, 802.1x, Trusted boot / execution / upgrade
Power supply type	12V DC / PoE(802.3af)
Power consumption	max 8.2W
Housing color	White
IP class	IP67
IK10	Yes
Working environment	-40°C~+60°C max 95% RH
Dimensions	Ø109.9.×81mm
Weight	0.35 kg
Box dimensions in mm (W×D×H)	138×137×115
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD Plus

BCS-L-DIP14FCR3L3-Ai1

Accessories

BCS-P-A173



BCS-UD3



BCS-ADU125



BCS-L-AD23



BCS-L-UD1

