

## BCS-L-TIP44VCR6L6-Ai1

Index: 12558

GTIN13/EAN13: 5904890714045

URL: <https://bcs.pl/gb/4mpx/4188-bcs-l-tip44vcr6l6-ai1-5904890714045.html>

## Product Details

|                  |                                                                     |
|------------------|---------------------------------------------------------------------|
| Product          | BCS-L-TIP44VCR6L6-Ai1                                               |
| Brand            | BCS LINE                                                            |
| Camera type      | Bullet                                                              |
| Resolution       | 4 Mpx                                                               |
| Sensor           | 1/2.9" CMOS                                                         |
| Scanning system  | Progressive Scan                                                    |
| Pixels           | 2688(H)×1520(V)                                                     |
| RAM              | 256MB                                                               |
| ROM              | 128MB                                                               |
| Lens             | motozoom                                                            |
| Focal length     | 2.7~13.5 mm                                                         |
| Aperture         | F1.5                                                                |
| Focus            | Auto / manual                                                       |
| Iris             | Auto                                                                |
| Optical zoom     | 5×                                                                  |
| Digital zoom     | 16×                                                                 |
| Angle of view    | H: 97°~28° V: 52°~16° D: 117°~32°                                   |
| DORI             | Detect 64~210m / Observe 26~84m / Recognize 13~42m / Identify 6~21m |
| Min illumination | 0.006Lux(Color,F1.5,30IRE) 0.0006Lux(B/W,F1.5,30IRE) 0Lux(IR)       |

|                                            |                                                                                                                                                                                                                                      |
|--------------------------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>S/N ratio</b>                           | 56dB                                                                                                                                                                                                                                 |
| <b>White balance</b>                       | (AWB) Auto / manual                                                                                                                                                                                                                  |
| <b>WDR</b>                                 | 120dB                                                                                                                                                                                                                                |
| <b>Backlight compensation</b>              | BLC / HLC / WDR(120dB)                                                                                                                                                                                                               |
| <b>Shutter</b>                             | Auto / manual 1/3~1/100000s                                                                                                                                                                                                          |
| <b>Gain control</b>                        | (AGC) Auto / manual                                                                                                                                                                                                                  |
| <b>Noise reduction</b>                     | 3D DNR                                                                                                                                                                                                                               |
| <b>Roi</b>                                 | Region of Interest                                                                                                                                                                                                                   |
| <b>Image rotate</b>                        | Mirror, Flip 0°/90°/180°/270°                                                                                                                                                                                                        |
| <b>Stream support</b>                      | 2                                                                                                                                                                                                                                    |
| <b>Resolutions</b>                         | 4M(2688×1520)(2560×1440) 3M(2304×1296) 2M(1920×1080) 1.3M(1280×960) 720P(1280×720)<br>D1(704×576/704×480) VGA(640×480) CIF(352×288/352×240)                                                                                          |
| <b>Main stream</b>                         | 2688×1520@(1~20fps ) 2560×1440@(1~25/30fps)                                                                                                                                                                                          |
| <b>Second stream</b>                       | 704×576(1~25fps) 704×480(1~30fps)                                                                                                                                                                                                    |
| <b>Bitrate</b>                             | H.264: 32 Kbps~6144 Kbps H.265: 12 Kbps~6144 Kbps                                                                                                                                                                                    |
| <b>Video compression</b>                   | H.265 / H.265+ / H.264 / H.264+ / MJPEG                                                                                                                                                                                              |
| <b>Day/night</b>                           | ICR mechanical infrared filter                                                                                                                                                                                                       |
| <b>Illuminator type</b>                    | IR LED + WhiteLight                                                                                                                                                                                                                  |
| <b>IR range</b>                            | 60m                                                                                                                                                                                                                                  |
| <b>WhiteLight range</b>                    | 60m                                                                                                                                                                                                                                  |
| <b>NightColor</b>                          | Yes                                                                                                                                                                                                                                  |
| <b>Microphone</b>                          | Yes                                                                                                                                                                                                                                  |
| <b>Audio in</b>                            | 1                                                                                                                                                                                                                                    |
| <b>Audio out</b>                           | 1                                                                                                                                                                                                                                    |
| <b>Audio compression</b>                   | G.711A / G.711Mu / G.726 / PCM                                                                                                                                                                                                       |
| <b>Alarm in</b>                            | 1                                                                                                                                                                                                                                    |
| <b>Alarm out</b>                           | 1                                                                                                                                                                                                                                    |
| <b>Storage</b>                             | FTP, SFTP                                                                                                                                                                                                                            |
| <b>Memory card slot</b>                    | microSD 256GB                                                                                                                                                                                                                        |
| <b>Support</b>                             | Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)                                                                                                                                                           |
| <b>Motion detect</b>                       | 4                                                                                                                                                                                                                                    |
| <b>Privacy masking</b>                     | 4                                                                                                                                                                                                                                    |
| <b>Network</b>                             | RJ-45 10/100 Mbps                                                                                                                                                                                                                    |
| <b>Compatibility</b>                       | ONVIF(S/G/T)                                                                                                                                                                                                                         |
| <b>Protocols</b>                           | IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, NTP, Multicast, ICMP, IGMP, P2P                                                                                                            |
| <b>Network security</b>                    | Video encryption, Configuration encryption, Digest, WSSE, Account lockout, Security logs, IP/MAC filtering, Generation and importing of X.509 certification, syslog, HTTPS, 802.1x, Trusted boot, Trusted execution, Trusted upgrade |
| <b>Power supply type</b>                   | 12VDC / PoE(802.3af)                                                                                                                                                                                                                 |
| <b>Power consumption</b>                   | max 12.7W                                                                                                                                                                                                                            |
| <b>Housing color</b>                       | White                                                                                                                                                                                                                                |
| <b>IP class</b>                            | IP67                                                                                                                                                                                                                                 |
| <b>Working environment</b>                 | -30°C~+60°C max 95% RH                                                                                                                                                                                                               |
| <b>Dimensions</b>                          | 238.5mm × 90.7mm × 90.7mm                                                                                                                                                                                                            |
| <b>Weight</b>                              | 0.76 kg                                                                                                                                                                                                                              |
| <b>Casing</b>                              | Metal                                                                                                                                                                                                                                |
| <b>Ai - Built-in intelligent functions</b> | Built-in intelligent algorithm of image analysis                                                                                                                                                                                     |
| <b>Ai - Perimeter protection</b>           | Crossline, intrusion                                                                                                                                                                                                                 |
| <b>Ai - Human/vehicle detection</b>        | Human/vehicle classification for crossline and intrusion reduces false alarms                                                                                                                                                        |
| <b>Ai - SMD - Smart Motion Detection</b>   | SMD Plus                                                                                                                                                                                                                             |



**Accessories**



BCS-ATU-B



BCS-AT135



BCS-AT356



BCS-AT5V



BCS-ADU-B



BCS-ADU100



BCS-ADU125