

BCS-L-TIP14FCL5-Ai1

Index: 12603

GTIN13/EAN13: 5904890714267

URL: <https://bcs.pl/gb/4mpx/4222-bcs-l-tip14fcl5-ai1-5904890714267.html>

Product Details

Product	BCS-L-TIP14FCL5-Ai1
Brand	BCS LINE
Camera type	Bullet
Resolution	4 Mpx
Sensor	1/1.8" CMOS
Scanning system	Progressive Scan
Pixels	2688(H)×1520(V)
RAM	256MB
ROM	128MB
Lens	fixed
Focal length	2.8 mm
Aperture	F1.0
Focus	fixed
Iris	fixed
Digital zoom	16×
Angle of view	H: 112° V: 60° D: 134°
DORI	Detect 58m/ Observe 23m/ Recognize 12m/ Identify 6m
Min illumination	0.0005Lux(Color,F1.0)
S/N ratio	56dB

White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
LDC	Lens Distortion Correction
Roi	Region of Interest
Image rotate	Mirror, Flip 0°/90°/180°/270°
Stream support	2
Resolutions	4M(2688×1520)(2560×1440) /3M(2304×1296) /2M(1920×1080) /1.3M(1280×960) /720P(1280×720) /D1(704×576/704×480) /VGA(640×480) /CIF(352×288/352×240)
Main stream	2688×1520(1~20fps) 2560×1440(1~25/30fps)
Second stream	704×576(1~25fps) 704×480(1~30fps)
Bitrate	H.264: 32 Kbps~6144 Kbps H.265: 12 Kbps~6144 Kbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	WhiteLight
WhiteLight range	50m
NightColor	NightColor 2.0
Microphone	Yes
Audio compression	G.711A / G.711Mu / G.726 / PCM
Storage	FTP, SFTP, NAS
Memory card slot	microSD 256GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, P2P, Bonjour, Auto Registration
Network security	Video / Firmware / Configuration encryption, Digest, WSSE, Account lockout, Security logs, IP/MAC filtering, Generation and importing of X.509 certification, syslog, HTTPS, 802.1x, Trusted boot / execution / upgrade, Session security, Security warning
Power supply type	12VDC / PoE(802.3af)
Power consumption	max 7.2W
Housing color	White
IP class	IP67
Working environment	-40°C~+60°C max 95% RH
Dimensions	197.9×80.2×76.2mm
Weight	0.57 kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD Plus

Accessories



BCS-AT135



BCS-AT3



BCS-AT356