

BCS-L-EIP46VCR4L4-Ai1



Index: 12547
GTIN13/EAN13: 5904890713932
URL: <https://bcs.pl/gb/6mpx/4179-bcs-l-eip46vcr4l4-ai1-5904890713932.html>




Product Details

Product	BCS-L-EIP46VCR4L4-Ai1
Brand	BCS LINE
Camera type	Dome
Resolution	6 Mpx
Sensor	1/2.7" CMOS
Scanning system	Progressive Scan
Pixels	3288(H)×1850(V)
RAM	256MB
ROM	128MB
Lens	motozoom
Focal length	2.7~13.5 mm
Aperture	F1.5
Focus	Auto / manual
Iris	Auto
Optical zoom	5×
Digital zoom	16×
Angle of view	H: 114°~32° V: 58°~17° D: 138°~36°
DORI	Detect 64~210m / Observe 26~84m / Recognize 13~42m / Identify 6~21m
Min illumination	0.007Lux(Color,F1.5,30IRE) 0.0007Lux(F1.5,B/W,30IRE) 0Lux(IR)

S/N ratio	56dB
White balance	(AWB) Auto / manual
WDR	120dB
Backlight compensation	BLC / HLC / WDR(120dB)
Shutter	Auto / manual 1/3~1/100000s
Gain control	(AGC) Auto / manual
Noise reduction	3D DNR
Roi	Region of Interest
Image rotate	Mirror, Flip 0°/90°(corridor mode)/180°/270°
Stream support	2
Resolutions	6M(3288×1850/3200×1800) 5M(2880×1620) 4M(2688×1520) 3M(2304×1296) 1080p(1920×1080) 1.3M(1280×960) 720p(1280×720) D1(704×576/704×480) VGA(640×480) CIF(352×288/352×240)
Main stream	3288×1850(1~20fps) 2688×1520(1~25/30fps)
Second stream	704×576(1~25fps) 704×480(1~30fps)
Bitrate	H.264: 32 Kbps~8192 Kbps H.265: 12 Kbps~8192 Kbps
Video compression	H.265 / H.265+ / H.264 / H.264+ / MJPEG
Day/night	ICR mechanical infrared filter
Illuminator type	IR LED + WhiteLight
IR range	40m
WhiteLight range	40m
NightColor	Yes
Microphone	Yes
Audio compression	G.711A / G.711Mu / G.726 / PCM
Storage	FTP, SFTP
Memory card slot	microSD 256GB
Support	Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	4
Privacy masking	4
Network	RJ-45 10/100 Mbps
Compatibility	ONVIF(S/G/T)
Protocols	IPv4, IPv6, HTTP, TCP, UDP, ARP, RTP, RTSP, RTCP, RTMP, SMTP, FTP, SFTP, DHCP, DNS, DDNS, QoS, UPnP, NTP, Multicast, ICMP, IGMP, NFS, PPPoE, Bonjour, P2P
Network security	Video/Firmware/Configuration encryption,Digest,WSSE,Account lockout,Security logs,IP/MAC filtering,Generation and importing of X.509 certification,syslog,HTTPS,802.1x,Trusted boot/execution/upgrade, Session security, Security warning
Power supply type	12VDC / PoE(802.3af)
Power consumption	max 10.1W
Housing color	White
IP class	IP67
Working environment	-30°C~+60°C max 95% RH
Dimensions	Ø122×108.3mm
Weight	0.7 kg
Ai - Built-in intelligent functions	Built-in intelligent algorithm of image analysis
Ai - Perimeter protection	Crossline, intrusion
Ai - Human/vehicle detection	Human/vehicle classification for crossline and intrusion reduces false alarms
Ai - SMD - Smart Motion Detection	SMD Plus

Accessories



BCS-AD2M3V



BCS-AT135



BCS-AT356



BCS-UD1



BCS-UD3