

BCS-L-NVR0401-4KE(2L)

Index: 12663

GTIN13/EAN13: 5904890714670

URL: <https://bcs.pl/gb/4-channel/4290-bcs-l-nvr0401-4ke2l-5904890714670.html>

Product Details

Product	BCS-L-NVR0401-4KE(2L)
Brand	BCS LINE
System	IP
Pentaplex function	Live view / recording / playback / archiving / remote access
Channels	4
HDD support	1
HDD capacity	20 TB
Record mode	Continuous, manual, alarm, motion detection, schedule, Ai
Max recording resolution	12 Mpx
Incoming bandwidth	80Mbps
Outgoing bandwidth	60Mbps
Recording bandwidth	80Mbps
Display efficiency	Ai Wył: 1× 12 M@30fps, 2× 8 M@30fps, 3× 5 M@30fps, 4× 4 M@30fps Ai Wł: 1× 12 M@30fps, 1× 8 M@30fps, 2× 5 M@30fps, 3× 4 M@30fps
Recording resolutions	12 M / 8 MP / 6 MP / 5 MP / 4 MP / 3 MP / 1080p / 960p / 720p / D1 / CIF / QCIF
Video compression	H.265+ / H265 / H.264+ / H.264 / MJPEG
HDMI out	HDMI4K
VGA out	VGA
HDMI display resolutions	Simultaneous with VGA: 3840×2160 / 1920×1080 / 1280×1024 / 1280×720 Independent VGA: 1920×1080 / 1280×1024 / 1280×720

VGA display resolutions	1920×1080 / 1280×1024 / 1280×720
Display split	1/4
Recording	continuous recording, with motion detection (with recording before and after detection), alarm (with pre- and post-alarm recording), cyclic (overwriting), Ai
Synchronous playback	1/4
Archiving	Possibility to download material to external media such as USB FLASH, USB HDD
Interfaces	2×USB2.0
Audio in	1
Audio out	1
Audio compression	G.711A / G.711U / G.726 / PCM
Alarm	Motion detection, signal lost,, sabotage, scene change, PIR, IPC, Ai functions, offline, HDD, IP, MAC, login
Support	Local, Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Network	RJ-45 10/100Mbps
Compatibility	ONVIF(S/G/T), support third party cameras
PTZ control	Intelligent 3D positioning with PTZ cameras BCS LINE series.
Protocols	HTTP, HTTPS, TCP/IP, IPv4, IPv6, UDP, NTP, DHCP, DNS, SMTP, UPnP, IP Filter, FTP, DDNS, SNMP, Alarm Server, P2P, Auto Registration, IP Search
Power supply	12V DC
Power consumption (without HDD)	max 10W
Working environment	-10°C~+55°C max 93% RH
Casing	1U
Dimensions (W×D×H)	260×232.5×47.6mm
Weight (without HDD)	0.81 kg
Ai - Intelligent functions from recorder	SMD Plus
Ai - Intelligent functions from camera	Face Detection, Face Identification, Perimeter Protection (Person/Vehicle Recognition), SMD Plus, People Counting, Heat Map
Ai - Perimeter protection	4 kanałów z kamer
Ai - Face detection	4 kanałów z kamer
Ai - Face recognition	4 kanałów z kamer
Ai - SMD - Smart Motion Detection	4 kanały z rejestratora (rozpoznawanie osoba/pojazd mechaniczny), 4 kanałów z kamer