

BCS-L-XVR0801-4KE(5)

Index: 12140

GTIN13/EAN13: 5904890712508

URL: <https://bcs.pl/gb/8-channel/3915-bcs-l-xvr0801-4ke5-5904890712508.html>

Product Details

Product	BCS-L-XVR0801-4KE(5)
Brand	BCS LINE
Transmission standard	HD-CVI / AHD / HD-TVI / ANALOG / IP
System	Analog HD + IP
Pentaplex function	Live view / recording / playback / archiving / remote access
Channels	8
HDD support	1
HDD capacity	16 TB
Max recording resolution	8 Mpx
Incoming bandwidth	128Mbps
Outgoing bandwidth	128Mbps
Recording bandwidth	128Mbps
HD-CVI camera	4K@25/30fps, 6MP@20fps, 5MP@20fps, 5MP@25fps, 4MP@25/30fps, 1080p@25/30fps, 720p@25/30fps, 720p@50/60fps
AHD camera	4K@15fps, 5MP@20fps, 4MP@25/30fps, 3MP@25/30fps, 1080p@25/30fps, 720p@25/30fps
HD-TVI camera	4K@15fps, 5MP@20fps, 4MP@25/30fps, 3MP@25/30fps, 1080p@25/30fps, 720p@25/30fps
ANALOG camera	CVBS PAL/NTSC
XVR - IP camera	8M
XVR - IP channels	8+8

Recording resolutions	8M / 6M / 5M / 4K Lite / 4M / 3M / 4M Lite / 1080P / 720P / 960H / D1 / CIF
Main stream	8M(7fps), 6M(10fps), 5M(12fps), 4K Lite/4M/3M(15fps), 4M Lite/1080P/720P/960H/D1/CIF(25/30fps)
Second stream	960H(15fps), D1/CIF(25/30fps)
Bitrate	32Kbps~6144Kbps
Video compression	H.265+ / H265 / H.264+ / H.264 / Ai coding
HDMI out	HDMI4K
VGA out	VGA
HDMI display resolutions	3840×2160 / 1920×1080 / 1280×1024 / 1280×720
VGA display resolutions	1920×1080 / 1280×1024 / 1280×720
Display split	1/4/8/9 (1/4/8/9/16 IP)
Synchronous playback	1/4/9
Archiving	Possibility to download material to external media such as USB FLASH, USB HDD
User connections	128
Interfaces	1×USB2.0, 1×USB3.0
Serial port	RS485
Audio in	1
Audio out	1
Audio compression	G.711A / G.711U / PCM
Support	Local, Web Service, CMS BCS Manager (Windows/Linux/MAC), Mobile App(iOS, android)
Motion detect	Areas: 396(22×18)
Privacy masking	4
Network	RJ-45(10/100/1000Mbps)
Compatibility	ONVIF
Protocols	HTTP, HTTPS, TCP / IP, IPv4, RTSP, UDP, SMTP, NTP, DHCP, DNS, DDNS, P2P
Power supply	12V DC
Power consumption (without HDD)	max 10W
Working environment	-10°C~+55°C max 90% RH
Casing	1U
Dimensions (W×D×H)	260×235×47mm
Weight (without HDD)	1 kg
POS	Yes
Ai - Built-in intelligent functions	Yes
Ai - Intelligent functions from recorder	Perimeter protection (human/vehicle recognition), smart motion detection (human/vehicle recognition), face detection, face recognition
Ai - Perimeter protection	8 channels analog HD
Ai - Face detection	2 channel analog HD, face attributes (gender, age, glasses, expression, mask, beard), max 12 pictures for second
Ai - Face recognition	2 analog HD channels, max. 8 images per second, up to 10 face databases, 20 thousand images
Ai - SMD - Smart Motion Detection	8 channels analog HD